

Sr600

COMPLETE COVERAGE IN-CAR VIDEO SOLUTION



SUMMARY

- In-vehicle video camera designed for public safety applications
- Single-lens 360° coverage, for complete situational context
- Secure Wi-Fi upload to CommandCentral Vault evidence management solution
- CJIS-compliant for court-admissible evidence quality
- Manual or automatic activation

OPTICS/LENS

| | |
|------------------------|------------------------------------|
| Lens Type | 8-Element Glass Ultra-Fisheye Lens |
| Aperture | f 2.5 |
| Field of View | 360° horizontal, 240° vertical |
| Effective Focal Length | 0.88 mm |
| Minimum Focus Distance | 30 cm |

FEATURES

| | |
|-------------------|---|
| External Triggers | Up to 8 wired triggers for automatic camera activation (lights/siren on, door open, airbag deployed, etc) |
| Keys | One Operation Key (Power On/Off, Recording Start/Stop) Two Programmable Buttons (Additional Functions such as Audio Mute, Covert Mode) |
| Status Indicator | Tri-color LED |
| Vibration Motor | For Haptic Feedback |
| Microphone | Built-in Dual Omni-Directional Microphones |
| Sensors | Accelerometer, E-Compass, Non-Assisted GPS, Gyroscope |
| Storage | Internal 128 GB Up to 10 hrs of recording at maximum resolution |
| Wi-Fi | 2.4 GHz and 5 GHz 802.11 b/g/n/ac |

ENVIRONMENTAL SPECIFICATIONS

| | |
|-----------------------|--|
| Protection Rating | IP67 (submersible up to 1 m for 30 mins) |
| Shock Resistance | Up to 1 m drop to concrete |
| Operating Temperature | -30 to 65 °C (-22 to 150 °F) |
| Storage Temperature | -40 to 85 °C (-40 to 185 °F) |

POWER

| | |
|------------------|-------------------------------|
| Power Supply | 5V USB or 12V Vehicular Power |
| Built-in Battery | 2100 mAh (2 hrs) for backup |

SIZE AND WEIGHT

| | |
|------------------|---|
| Dimensions | 2.3 x 1.5 x 5.3 in (58 x 38 x 108 mm), W x H x D |
| Weight | 5.9 oz (167 g) |
| Mounting options | Permanent adhesive windshield mount (standard) Suction cup windshield mount (optional) |

RECORDING

| | |
|----------------------|--|
| Video Format | MPEG4, encrypted, incorporating GPS co-ordinate data |
| Video Resolution | 480p, 720p, 1080p, 2880x2880 (4K) |
| Video Recording Rate | 30 fps |
| Audio Format | Stereo, 48 kHz, 96 kbps AAC |

BAYCOM info@baycominc.com
800-726-5426



Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. motorolasolutions.com

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2017 Motorola Solutions, Inc. All rights reserved. 08-2017